



S.C. RAFINĂRIA STEAUA ROMÂNĂ S.A.

CÂMPINA, CALEA DOFTANEI NR. 15, 105600
Prahova, ROMÂNIA

Tel: (+40) 244 336 151 ♦ Fax: (+40)2 44 337 341

E-mail: steauaromana@steauaromana.ro; www.steauaromana.ro



DA COMPONENT (ST 3/2003) Custom code 2710.11.25

TECHNICAL SPECIFICATIONS:

CHARACTERISTICS	QUALITY TECHNICAL CONDITIONS	ANALYSIS METHOD	
		STAS	ASTM
Density at 15 °C, g/cm ³ , max .	0.760	35-81	D 1298-85
Water and impurities	absence	24/1-1989	D 96 / 88
Distillation, °C			
- initial boiling point °C min.	35	SR ISO 3405-98	D 664 / 95
- 50% vol until °C max.	140		
- 90% vol until °C max.	185		
Mineral acidity and alkalinity	absence	22-64	D 664 / 95
Aromatic hydro-carburant	22	8852 / 72	D 875 / 64

GENERAL DESCRIPTION:

Present specification are referring to the **DA COMPONENT** produced from gasoline fractions obtained by primary distillation.

APPLICATIONS:

This product is used as organic solvent, diluents as per stipulations, metal parts washing, degreasing, etc.

End users are sole responsible for not using the product in accordance with producer's prescriptions and import country legislation in force.

PACKAGING – STORAGE:

The packaging, marking and storage shall be made as per stipulations of Romanian standard STAS 4225/79.

Product is delivered in clean suitable means of transport, each lot being accompanied by quality, quantity certificates and transport safety data sheet.

Quality is guaranteed for 3 (three) months starting from producing date, stipulated storing conditions have to be observed.

SAFETY MEASURES:

As product is flammable, usual caution measures of fire prevention have to be taken when handling and storing this product.

Note: The info in this technical sheet is valid until the 31st of December, 2008. We ask you to contact STEAUA ROMANA REFINERY in order to see if the document has been revised .