



S.C. RAFINĂRIA STEAUA ROMÂNĂ S.A.

CÂMPINA, CALEA DOFTANEI NR. 15, 105600
Prahova, ROMÂNIA

Tel: (+40) 244 336 151 ♦ Fax: (+40)2 44 337 341

E-mail: steauaromana@steauaromana.ro; www.steauaromana.ro



DILUSTAR (ST 1/2004) Custom code: 3814.00.90

TECHNICAL SPECIFICATION:

CHARACTERISTICS	QUALITY TECHNICAL CONDITIONS	TEST METHOD		
		STAS	ISO	ASTM
Density at 15°C, g/cm ³ , max.	0.810	35-81	3675	D 1298 / 85
Ignition point AP, min, °C	30	SR ISO 13736-2001	13736	D 93 / 97
Distillation: - initial, °C, max. - % vol., up to 250°C, min.	160 85	SR ISO 3405	3405 / 98	D 86 / 96
Water, % gr, max.	0.1	24/2-89	3733	D 95 / 83
Mechanical impurities	absence	33-84	-	-
Neutralization index, KOH/100 cm ³ max.	4	23-81	6618	D 974 / 97
Sulphur, % max.	0.1	SR ISO 8754	8754 / 96	D 4294 / 90
Acidity and mineralalkalinity	Absence	22-64	-	D 664 / 95

GENERAL DESCRIPTION:

Present specs are referring to the **DILUSTAR** obtained by primary distillation of crude oil. The product contains chlorinated products (dicloropropane) and xylene.

APPLICATIONS:

This product can be used as an organic solvent (dilutor) in dye and varnish industry, rubber industry and in conditioning and producing of insecticides.

End users are sole responsible for not using the product in accordance with producer's prescriptions and import country legislation in force.

PACKAGING-STORAGE:

The packaging, marking and storage shall be made as per stipulations of Romanian standard STAS 4225/79.

Product has to be delivered only in clean suitable means of transportation, each lot being accompanied by quality, quantity certificates and transport safety data sheet. Quality is guaranteed for 3 (three) months starting from producing date, stipulated storage conditions have to be observed.

SAFETY MEASURES:

As product is flammable, usual cautionary measures of fire preventing are to be taken when handling and storing the product.

Note: The info in this technical sheet is valid until the 31st of December, 2008. We ask you to contact STEAUA ROMANA REFINERY in order to see if the document has been revised .