



S.C. RAFINĂRIA STEAUA ROMÂNĂ S.A.

CÂMPINA, CALEA DOFTANEI NR. 15, 2150
Prahova, ROMÂNIA

Tel: (+40) 244 336 151 ♦ Fax: (+40)2 44 337 341

E-mail: steauaromana@steauaromana.ro; www.steauaromana.ro



LS V.G.O. (VACUUM GAS OIL)

ST 6/2002

Custom code: 2710.19.71

TECHNICAL SPECIFICATIONS:

CHARACTERISTICS	TECHNICAL CONDITIONS	TEST METHODS		
		STAS	ISO	ASTM
Density at 15 °C, max.	0,920	35 – 81	3675	D 1298/85
Viscosity at 100 °C , ° E, min	1.2	117 - 87	3104	D 445/96
Pouring point °C max.	+55	37-67	2176	D 566/93
Conradson coke, %gr max	1.0	SR ISO 6615	6615-96	D 189/97
Flammability point °C,min	100	5489-80	2719-88	D 92/97
Water, %,max	0,1	24/2-89	3733	D 95/83
Mineral acidity and alkalinity	Absence	22-64	-	D 664/95
Sulphur, %,max	1	SR ISO 8754-96	8754-96	D 4294/90
Distil: initial point, ° C, min	225	SR ISO 3405	3405-98	D 86/96

GENERAL DESCRIPTION:

Present specification are referring to the **VACUUM DISTILLATE (LS VGO)** produced from parafinic fractions , obtained by vacuum distillation of parafinous fuel oils .

APPLICATIONS:

This product is used as raw material for catalytic reforming .

End users are sole responsible for not using the product in accordance with producer's prescriptions and import country legislation in force.

PACKAGING – STORAGE:

The packaging, marking and storage shall be made as per stipulations of Romanian standard STAS 4225/79.

PACKAGING – STORAGE:

The packaging, marking and storage shall be made as per stipulations of Romanian standard STAS 4225/79. Product is supplied by suitable transport means, each lot being accompanied by quality, quantity certificates and transport safety data sheet.

Quality is guaranteed for 3 (three) months starting from producing date, stipulated storage conditions have to be observed.

SAFETY MEASURES:

As product is flammable, usual caution measures of fire prevention have to be taken when handling and storing this product.

Note: The info in this technical sheet is valid until the 31st of December, 2008. We ask you to contact STEAUA ROMANA REFINERY in order to see if the document has been revised .